

Pressio® 4 cables® UNIVERSAL VA - Onion ring technology			
Ø in mm	Product	Art.-No.	
50		<p><b>Pressio® 4 cables® UNIVERSAL VA OD 50 mm / 2x 6-16 mm, closed</b></p> <p>Pressure rating: 1.5 bar</p> <p>Supplied incl. blind plugs</p>	11011
100		<p><b>Pressio® 4 cables® UNIVERSAL VA OD 100 mm / 18-65 mm, closed</b></p> <p>Possible cables-Ø: 18 up to 65 mm (in 5 mm steps per ring)</p> <p>Pressure rating: 1.5 bar</p> <p>Supplied incl. blind plug</p>	10490
100		<p><b>Pressio® 4 cables® UNIVERSAL VA OD 100 mm / 18-20, 25, 32, 40, 50, 63 mm, split</b></p> <p>Pressure rating: 1.5 bar</p> <p>Supplied incl. blind plug</p>	10499
100		<p><b>Pressio® 4 cables® UNIVERSAL VA OD 100 mm / 4x 6-30 mm, split, EPDM</b></p> <p>ID slats: 4x 6, 10, 14, 18, 22, 26, 30 mm (sealing range from 3.5 mm upward)</p> <p>Pressure rating: 1.0 bar</p> <p>Supplied incl. 4 pcs. blind plugs</p>	11020
		<p><b>Identical in construction, rubber NBR</b></p>	11024
100		<p><b>Pressio® 4 cables® UNIVERSAL VA OD 100 mm / 2x 6-32 mm, 2x 6-26 mm, split</b></p> <p>ID slats: 2x 6, 10, 14, 18, 22, 26, 30, <b>32 mm</b> 2x 6, 10, 14, 18, 22, <b>26 mm</b> (sealing range from 3.5 mm upward)</p> <p>Pressure rating: 1.0 bar</p> <p>Supplied incl. 4 pcs. blind plugs</p>	11021
100		<p><b>Pressio® 4 cables® UNIVERSAL VA OD 100 mm / 25-50 mm, 2x 6-16 mm, closed</b></p> <p>ID slats: 25, 30, 35, 40, 45, 50 mm 2x 10, 16 mm (sealing range from 6 mm upward)</p> <p>Pressure rating: 1.0 bar</p> <p>Supplied incl. blind plugs</p>	11014

Pressio® 4 cables® UNIVERSAL VA - Onion ring technology			
Ø in mm	Product		Art.-No.
150	 	<p><b>Pressio® 4 cables® UNIVERSAL VA</b>  <b>OD 150 mm / 32, 40, 50, 63, 76, 90, 110 mm, closed</b></p> <p>Possible cables-Ø: 32, 40, 50, 60.3 up to 63 mm,  75 up to 76.1 mm,  88.9 up to 90 mm, 110 mm</p> <p>Pressure rating as  blind closure: for low external water pressure  Pressure rating with  cable/carrier pipe: 1.0 bar</p> <p>Supplied incl. blind plug</p>	10495
150		<p><b>Pressio® 4 cables® UNIVERSAL VA</b>  <b>OD 150 mm / 3x 25-50 mm, closed</b></p> <p>ID slats: each 25, 30, 35, 40, 45, 50 mm  (sealing range from 22 mm upward)</p> <p>Pressure rating: 1.0 bar</p> <p>Supplied incl. blind plugs</p>	11025
150		<p><b>Pressio® 4 cables® UNIVERSAL VA</b>  <b>OD 150 mm / 3x 25-50 mm, split</b></p> <p>ID slats: each 25, 30, 35, 40, 45, 50 mm  (sealing range from 22 mm upward)</p> <p>Pressure rating: 1.0 bar</p> <p>Supplied incl. blind plugs</p>	11026
150		<p><b>Pressio® 4 cables® UNIVERSAL VA</b>  <b>OD 150 mm / 7x 5-32 mm, split</b></p> <p>ID slats: each 5, 10, 15, 20, 25, 32 mm  (sealing range from 3 mm upward)</p> <p>Pressure rating: 1.0 bar</p> <p>Supplied incl. blind plugs</p>	11027
200		<p><b>Pressio® 4 cables® UNIVERSAL VA</b>  <b>OD 200 mm / 110, 125, 140, 160 mm, closed</b></p> <p>Possible cables-Ø: 110, 125 mm  139.7 up to 140 mm, 160 mm</p> <p>Pressure rating as  blind closure: for low external water pressure  Pressure rating with  cable/carrier pipe: 1.0 bar</p> <p>Supplied incl. blind plug</p>	10493
200		<p><b>Pressio® 4 cables® UNIVERSAL VA</b>  <b>OD 200 mm / 3x 25-50 mm, 4x 5-32 mm, split</b></p> <p>ID slats DN 50: each 25, 30, 35, 40, 45, 50 mm  (sealing range from 22 mm upward)</p> <p>ID slats DN 32: each 5, 10, 15, 20, 25, 30 mm  (sealing range from 3 mm upward)</p> <p>Pressure rating: 1.0 bar</p> <p>Supplied incl. blind plugs</p>	11028