1K Beto-coat 4 pipes







1K Beto-coat 4 pipes is a high quality coating for surfaces, especially concrete, stonework, steel and other materials. Core drilled holes at wall penetrations are coated to avoid entry of water into the wall.

1K Beto-coat 4 pipes comes in a kit which is **suitable for sites**, including safety gloves and an application brush. It consists of an alkyd-epoxy resin mixture and binds exceptionally strongly to the substrate. Good filling and covering capacity, rust-blocking, anti-corrosive, ventilating, productive.

As a one-component system, the can is **resealable after use** and the remaining container can be **used for the next application**.



1K Beto-coat 4 pipes can be applied with a brush, roller or by spraying. The surface must be clean, free of grease and dust. Use on a slightly damp surface is possible.

Before applying, stir the contents of the can well until the resin mixture appears homogeneous. After that, the coating is applied on the surface. At least two layers of 1K Beto-coat are required to achieve the full coating quality.

Technical data

Drying time	dust-dry after 30-45 minutes, able to paint over after 2-3 hours, nitro tight after 12 hours
Coverage	approx. 5 m² per litre
Thinner	use universal thinner to spray and clean the equipment

Safety instructions

Use only in well-ventilated rooms. Do not inhale spray. Avoid contact with eyes. Keep out of the reach of children. Do not pour into drains. Flammable.Safety data sheet on request.









