

SuperSeal™

Heat shrinkable sleeve for protection of pre-insulated pipe joints



SuperSeal™ is a high performance, heat shrinkable product intended for sealing of pre-insulated pipe joints. SuperSeal™ provides superior barrier against moisture ingress while protecting the joints from the soil stresses associated with Pre-Insulated Pipelines.

Specifically designed for bonding to polyethylene pipes and casings, SuperSeal™ offers low substrate pre-heat temperature thus making the installation of this product simple, forgiving, and most importantly, reliable.

Effective Long Term Sealing

- A combination of cross-linked, Bi-modal HDPE backing with a layer of unique hot melt adhesive, results in a long term barrier impermeable to moisture.
- SuperSeal™ complies with the stringent requirements of the EN 489 standard.

Proven Track Record

- SuperSeal™ has been protecting joints of pre-insulated pipelines for over 25 years

Reliable and Consistent Performance

- Low installation pre-heat temperature ensures forgiving and thus repeatable installation
- High performance backing provides superior mechanical strength required for high stress environments

Flexible Product Options Save Time and Money

- Available in two configurations: pre-cut to specific pipe size and bulk rolls
- Allows for lower inventories of pre-cut sleeves and just-in-time sleeve cutting, thus reducing cost



Applications

-  Pre-Insulated Pipes
-  Foam-In-Place
-  Pre-Foamed Joints



SuperSeal™

Heat shrinkable sleeve for protection of pre-insulated pipe joints



Adhesive Properties	Test Method	Typical Values	
Softening Point	ASTM E28	90°C	
Lap Shear @ 23°C	ISO 21809-3	225 N/cm ²	
Backing Properties			
Tensile Strength	ASTM D638	26 MPa	
Elongation	ASTM D638	600	
Hardness	ASTM 2240	60 Shore D	
Specific Gravity	ISO 1183	0.94	
Sleeve Properties			
Adhesion Strength @ 23°C	ISO 21809-3	100 N/cm	
Water Absorption	ASTM D570	0.05 %	
Low Temp. Flexibility	ASTM D2671	-30°C	
Soil Box & Pressure Vessel Test	EN 489	100 cycles, 30 kPa @ 30°C for 24 h*	
Thickness	T	1.75	L
Backing (nominal thickness as supplied)	0.6 mm	0.75	0.9 mm
Adhesive (nominal thickness as supplied)	0.9 mm	1.0	1.3 mm

Effective
long term sealing

Over 15 years of
in service sealing

* Applies to 1.75 and L configurations

Since 1967, Canusa-CPS has been a leading developer and manufacturer of specialty pipeline coatings for the sealing and corrosion protection of pipeline joints and other substrates. Canusa-CPS high performance products are manufactured to the highest quality standards and are available in a number of configurations to accommodate many specific project applications.